



A Moen Incorporated Brand



Models:
CA47211 2H Lav with 50/50 waste
CA47212 2H Lav less waste



Two Handle Lavatory With Waste

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections
- Will accept standard cone/bevelled connection for 3/8" tubing
- Includes 50-50 pop-up type waste assembly where noted
- Six (6) individual boxes per master carton
- International red/blue markings

OPERATION

- Lever style handles
- **Hot side:** Turn counterclockwise to open (clockwise to close)
- **Cold side:** Turn clockwise to open (counterclockwise to close)

FLOW

- Flow is limited to 1.5 gpm max. (5.7L/min) at 60 psi, for products made before October 2008 flow is limited to 2.2 gpm max. (8.3L/min)

CRITICAL DIMENSIONS

- **Note:** This faucet is designed to be installed through 3 holes, 1" minimum diameter, 4" centers
- Maximum deck thickness 0.875" (22.2 mm)

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and brass material
- Single body construction for easy replacement

STANDARDS

- Third party certified to WaterSense® CSA B125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and the Federal Safe Water Drinking Act
- ADA for lever handles

WARRANTY – RESIDENTIAL, COMMERCIAL

- One year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

