



A Moen Incorporated Brand



One Handle Kitchen With Spray

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Hose reach 34", hose length 48", Hydrolock® Connection (for models built after November 2010)
- 40513: Chrome finish, white spray, white spray escutcheon
- 40513B: Chrome finish, black spray, black spray escutcheon
- 40513C: Chrome finish, chrome spray, chrome spray escutcheon
- 40513SL: Stainless finish, stainless spray, stainless spray escutcheon
- 1/2" IPS connections
- Six (6) individual boxes per master carton

OPERATION

- Pivot action, lever-style handle
- Temperature control by 90° arc
- Will operate with less than 5 lbs. of force

FLOW

- Aerator limited to 2.2 gpm (8.3 L/min)

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and plastic material
- Single body construction for easy replacement

NOTE

- 40513 series is designed to install through 4 holes 1-1/4" (32mm) MIN. DIA. and 4" (102mm) on center

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein, including NSF61/9
- Complies with California Proposition 65, and the Federal Safe Drinking Water Act
- Feature red/blue hot/cold temperature indicators
- ADA for lever handle

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

