



A Moen Incorporated Brand

Model: **40712 series 1H LAV with 50/50 Waste**  
**40718 series 1H LAV with All Metal Waste**  
**40719 series 1H LAV Less Waste**



## One Handle Lavatory With Quick Install Flexible Supply Lines

### DESCRIPTION

- Metal construction with various finishes identified by suffix
- Includes all metal 17ga brass or 50/50 pop-up type waste assembly where noted
- Flexible supplies with 3/8" compression fittings
- Six (6) individual boxes per master carton

### OPERATION

- Pivot action lever-style handle
- Temperature control by 90° arc
- Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handle

### FLOW

- Flow is limited to 1.5 gpm max. (5.7L/min) at 60 psi, for products made before October 2008 flow is limited to 2.2 gpm max. (8.3L/min)

### CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and plastic material
- Single body construction for easy replacement

### NOTE

- This faucet is designed to be installed through 3 holes, 1" minimum diameter, 4" centers
- Maximum deck thickness 1.375" (35 mm) - Spacer provided, discard spacer if deck thickness exceeds 0.625" (15.9 mm)

### STANDARDS

- Third party certified to WaterSense® CSA B125.1, ASME A112.18.1, ICC A117.1, ANSI/NSF 61/9, IAPMO, and all applicable requirements referenced therein, the Federal Safe Drinking Water Act, California Proposition 65, Illinois, Massachusetts, and Texas
- Contains no more than 0.25% weighted average lead content
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Features red/blue hot/cold temperature indicators

### WARRANTY — RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

